

UPM Raflatac Technical Information

20-02-2022 EN SI

Face	PET WHITE TC 50
Sales Code	AJ
Product	White, matt, top-coated polyester film.
Use	Designed for durable labelling applications with good print resistance against chemicals, UV-light, heat and moisture.

Typical technical values

Substance	55	g/m ²	DIN 53352
Caliper	50	µm	DIN 53370
Opacity	92	%	ISO 2471
Gloss	13	%	ASTM D2457
Printability	Suitable for flexography, screen and offset printing methods. Special inks designed for non-absorbent materials should be used. Thermal transfer is possible with selected wax, wax-resin and resin ribbons.		
Advantages	Good dimensional stability. High tensile strength and stiffness. High tear strength. Very good heat resistance.		
Additional info	Manufactured from a minimum of 25% recycled PET resin from post consumer waste (PET bottles).		
Disclaimer	The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.		

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.