

## UPM Raflatac Technical Information

13-03-2022 EN SI

Backing	PET 50
Sales Code	HAG
Product	Clear polyester backing material.
Use	Designed for high-speed converting and label application lines, especially applications using small labels, which require an excellent stretch resistance to avoid wrongly labeled containers. High compression properties allow high die-cutting pressure for difficult label shapes. The high stiffness gives good stability in manual dispensing. Offers also excellent clarity with clear filmic faces.

### Typical technical values

Substance	70	g/m <sup>2</sup>	ISO 536
Caliper	50	µm	ISO 534
Tensile strength MD	9.3	kN/m	ASTM D-882
Tensile strength CD	9.3	kN/m	ASTM D-882

**Disclaimer**

The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.