

# Product Data

## Fasson® PRIMAX / PERMANENT (S692N)

---

Product Identification Number: BW0074

### Facestock:

**Fasson® PRIMAX :** A corona- treated flexible opaque white olefin film with good dimensional stability  
**Calliper :** 0.077mm  $\pm$  10% ( ISO 534 )

### Adhesive:

**Fasson® S692 N :** A clear permanent adhesive featuring excellent UV resistance and weatherability together with good adhesion performance ,even on apolar substrates

**Minimum Application Temperature :** 5° C  
*(The minimum temperature at which the label can be applied and will adhere)*

**Service Temperature Range :** - 20° C to + 80° C  
*(The temperature range to which the label can be exposed after the adhesion bond to the substrate has been formed)*

### Liner:

**Fasson® BG40:** A white glassine paper with excellent strength characteristics.  
**Basis Weight :** 62 gsm  $\pm$  10% (ISO 536) **Transparency :** 46% (DIN 53147)

**Total Construction Caliper:** 0.140 mm  $\pm$  10%

**Application and Use :** Applications are predominantly in cosmetics and toiletries ,areas requiring high quality graphics together with consistent functional performance during automatic application.  
S692 N adhesive is in compliance with German BgVV recommendations for use in indirect food contact.

**Conversion :** **Fasson® PRIMAX** product can be printed Flexo,Screen and UV letterpress giving good results with solvent ,UV and water based inks. Use of inline corona will expand the number of inks that can be used. It can be die-cut and stripped at high speeds using film tooling.

**Shelf Life :** One year when stored at 22° C / 50% RH.

*As with all self-adhesive materials, this product should be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.*