## **Zebra AN720 Rugged Indoor and Outdoor RFID Antenna**



## **AN720**

Description	Industrial, rugged, small form-factor, wide-beam width antenna Ideal for indoor or outdoor use in harsh environments such as: dock doors, gated access control, outdoor storage locations, etc.
Features	Industrial class, IP67 rated Wide beam-width of 100 degrees for wider coverage Ideal for short-range applications to create targeted zones
Applications	Suitable for use in indoor and outdoor environments Indoors: doorways, shelves, end-cap displays Outdoors: doorways, small conveyors
Part Number	AN720-L51NF00WUS AN720-L51NF00WEU

Physical	Dimensions Without	132.8 mm L x 132.8 mm W x 18.1 mm D	
	Mounting Screws	5.2 in. L x 5.2 in. W x 0.7 in. D	
	Dimensions with mounting screws	N/A	
	Connector	N-Type Female	
	Connector Location	Rear	
	Mounting Options	Articulating mounting bracket included	
	Weight	0.37 kg/0.8 lbs	
	Casing/Materials	Aluminum with white plastic cover	
	Frequency Range	EU: 865–868 MHz	US: 902-928 MHz
	Gain	EU: 3.5 dBiL	US/Canada: 3.0 dE
	VSWR (Return Loss)	1.5:1	
Outsetional	Front-to-Back Ratio	8 dB	
Operational	Polarization	Left-hand circular	
	3 dB Beam Width	100° in both planes	
	Max Power	10 Watts	
	Axial Ratio	2 dB	
	Operating Temperature	-25° to +70°C	-13° to +158°F
	IP Sealing	IP67	
Environmental	Storage Temperature	-40° to +70°C	-40° to +158°F
	Vibration	MIL-STD-810	
	Humidity	IEC-68-2-30	

ZEBRA TECHNOLOGIES

SiL 15